

Nedcon is an international Group engaged in the design, production and installation of industrial racking systems.

Storage meets intelligence:

Our solutions support your company strategy and organization. As our customer, you will be able to take advantage of the worldwide experience we have acquired since 1969, our knowledge in business, and our solution-focused design and engineering.

In addition to offices in several European countries and the US, Nedcon also benefits from a large reseller organization.



Nedcon Archive Rack

The Nedcon shelving rack range has been extended with a dedicated archive racking system. Due to the optimized design, the archive rack is perfectly suited for storing your folders and boxed files.

Lighter parts and smart innovations create a maximum of storage space using a minimum of racking material. Thus enabling you to maximize your archive storage capacity.

Storage meets intelligence

With the Nedcon Archive Rack we have extended the potential of our existing speedframe technology. Storage and intelligence met again to create a small racking system highly suited for the storage of your archive. The system uses little parts, provides ample storage space and can be made to fit practically everywhere. In your office or in a separated storage location the Nedcon Archive Rack will hold things together for your company.

We are certain our archive rack can compete with the best and is able to meet your every archiving need.

Getting to know our new system

Shelf length:	970 mm
Shelf height:	30 mm
Upright length:	2000, 2200 and 2500 mm
Frame/shelf depth:	300 and 400 mm (other lengths and depths on request)
Frame type:	braced or closed
Upright thickness:	1.0 mm, sendzimir (epoxy powder coated on request)
Shelf thickness:	0.6 mm, epoxy powder coated or sendzimir
Back bracing:	wire bracing (easy installation)
Base plate:	integrated in frame (no installation)

Maximum allowable load per racking section

(without load on bottom shelf)

Frame depth:	300 or 400 mm
Frame height:	2000 mm: 790 kg 2200 mm: 680 kg 2500 mm: 530 kg
Shelf capacity:	60 kg per shelf

Assumed design parameters

- frame arrangement 450-2 (frame depth 300 mm)
600-2 (frame depth 400 mm or more)
- max. distance between shelves 550 mm (top-to-top)
- max. 9 sections are braced by 1 vertical bracing cross
- sway imperfection of 1/200 in both directions
- placement load of 50 N in both directions
- pre-stressing force in bracing diagonal max. 600 N
- valid for FEM, GSF, DIN
- includes the effect of flexural-torsional buckling



Nedcon Magazijninrichting B.V.

Nijverheidsweg 26
7005 BJ Doetinchem
P.O. Box 35
7000 AA Doetinchem
The Netherlands
T +31 314 33 44 55
F +31 314 37 94 44
E info@nedcon.com